

Declaration of performance

№ 160/2020

According to Construction Products Regulation EU № 305/2011

1. *Unique identification code of the product-type:*
SensoIRIS MC-D
2. *Type Number:* **SensoIRIS MC-D**

Description: **Module conventional zone with built-in isolator module**
3. *Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer*
Fire detection and fire alarm systems installed in and around buildings
4. *Manufacturer*
**Teletek Electronics JSC
14A Srebarna Str.
1407 Sofia, Bulgaria**
5. *Trading Company*
**Teletek Electronics JSC
14A Srebarna Str.
1407 Sofia, Bulgaria**
6. *System of assessment*
System 1
7. *Notified Body*
**EVPU a.s.
19 Trencianska Str.
018 51 Nova Dubnica, Slovakia**

Notified Body Number **1293**

Performed **the prescribed tests and evaluation of factory production control according to system 4 and issued the following certificate**

EC Certificate Number **1293- CPR-0701**

8. *No European Technical Assessment has been issued for this product.*

9. *Declared performance*

| Essential characteristics | Performance | Harmonized technical specification EN 54-18:2005 EN 54-18:2005/AC:2007 |
|--|--------------------|---|
| Response delay (response time) | Pass | 5.2 |
| Operational reliability | Pass | 5.1.4 |
| Performance under fire conditions | Pass | 5.1.4 |
| Durability of operational reliability: temperature resistance | Pass | 5.3, 5.4 |
| Durability of operational reliability; vibration resistance | Pass | 5.8 to 5.11 |
| Durability of operational reliability; humidity resistance | Pass | 5.5, 5.6 |
| Durability of operational reliability; corrosion resistance | Pass | 5.7 |
| Durability of operational reliability; electrical stability | Pass | 5.2, 5.12 |

| Essential characteristics | Performance | Harmonized technical specification EN 54-17:2005 EN 54-17:2005/AC:2007 |
|--|--------------------|---|
| Performance under fire conditions | Pass | 5.2 |
| Operational reliability | Pass | 4 |
| Durability of operational reliability and response delay: temperature resistance | Pass | 5.4, 5.5 |
| Durability of operational reliability: humidity resistance | Pass | 5.6, 5.7 |
| Durability of operational reliability: shock and vibration resistance | Pass | 5.9 to 5.12 |
| Durability of operational reliability: corrosion resistance | Pass | 5.8 |
| Durability of operational reliability: electrical stability | Pass | 5.3, 5.13 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

1407 Sofia,
14A, Srebarna Str.
11.11.2020

Yuliy Iliev
Quality Manager

